



ORDERING NUMBER	DESCRIPTION	LENGTH
02-10-0013-12	TMS COMPONENT ASSEMBLY BOLT,MJ4 X 0.7 MM, 12MM LG	12MM
02-10-0013-18	TMS COMPONENT ASSEMBLY BOLT,MJ4 X 0.7 MM, 18MM LG	18MM
02-10-0013-25	TMS COMPONENT ASSEMBLY BOLT,MJ4 X 0.7 MM, 25MM LG	25MM
02-10-0013-30	TMS COMPONENT ASSEMBLY BOLT,MJ4 X 0.7 MM, 30MM LG	30MM

- NOTES:
- DRAWINGS FOR SPECIFICATION PURPOSES AND ARE FOR REFERENCE ONLY.
 - ALL VERSIONS OF THE DRAWING ARE SUPERSEDED BY THIS RELEASE AND SUBJECT TO CHANGE WITHOUT NOTIFICATION.
 - MATERIAL: A286; PER AMS 5731, AMS 5732, AMS 5734, AMS 5737, MINIMUM TENSILE STRENGTH IS 1,100 MPa MIN PER FF-S-86.
 - SOCKET HEAD CAP SCREW BASIC REQUIREMENTS; PER NAO069.
 - PTFE ELECTROLESS NICKEL PLATE.

EFFECTIVE DATE: 2/6/2017	<p>1003 INDUSTRIAL DRIVE SAUK RAPIDS, MN 56379 VOICE: 320-251-0390 FAX: 320-251-5810</p>
INTERPRET DRAWING PER: ASME Y14.5-2009	
THIRD ANGLE PROJECTION	
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TALON INNOVATIONS, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TALON INNOVATIONS, INC. IS PROHIBITED.	DESCRIPTION: TMS COMPONENT ASSEMBLY BOLT, MJ4 X 0.7 MM
DO NOT SCALE DRAWING	SCALE: 4:1 SHEET 1 OF 1