



ORDERING NUMBER	DESCRIPTION	LENGTH
02-10-0025-12	TALON ASSEMBLY BOLT, M5 X 0.8 MM, 12MM LG	12MM
02-10-0025-14	TALON ASSEMBLY BOLT, M5 X .08 MM, 14MM LG	14MM
02-10-0025-30	TALON ASSEMBLY BOLT, M5 X .08 MM, 30MM LG	30MM
02-10-0025-32	TALON ASSEMBLY BOLT, M5 X .08 MM, 32MM LG	32MM

- NOTES:
1. DRAWINGS FOR SPECIFICATION PURPOSES AND ARE FOR REFERENCE ONLY.
 2. ALL VERSIONS OF THE DRAWING ARE SUPERSEDED BY THIS RELEASE AND SUBJECT TO CHANGE WITHOUT NOTIFICATION.
 3. MATERIAL: TYPE 316 OR 18-8 STAINLESS STEEL, MINIMUM TENSILE STRENGTH IS 100,000 PSI.
 4. DIMENSIONAL SPECIFICATIONS ARE IN ACCORDANCE WITH DIN 912/ISO 4762 STANDARD AND HAVE CLASS 6G THREAD FIT.

EFFECTIVE DATE: 2/6/2017	<p>1003 INDUSTRIAL DRIVE SAUK RAPIDS, MN 56379 VOICE: 320-251-0390 FAX: 320-251-5810</p>
INTERPRET DRAWING PER: ASME Y14.5 - 2009	
THIRD ANGLE PROJECTION:	
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TALON INNOVATIONS, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TALON INNOVATIONS, INC. IS PROHIBITED.	DESCRIPTION: TALON CRADLE ASSEMBLY BOLT, M5 X 0.8 MM
SIZE: C	PART NUMBER: 02-10-0025-XX
DO NOT SCALE DRAWING	SCALE: 4:1 SHEET 1 OF 1